


# 33-38XL

## TRUCK OR TRACTOR-TOWED SCRAPER




MOBILE TRACK SOLUTIONS





# 33-38XL

## TRUCK OR TRACTOR-TOWED SCRAPER



### SCRAPER BOWL

ISO Capacity	35.9 yd <sup>3</sup>	27.45 m <sup>3</sup>
ISO Capacity - Sideracks	38.8 yd <sup>3</sup>	29.66 m <sup>3</sup>
Width of Cut, To Router Bits	157.5 in	4,000 mm
Capacity Struck	20.1 yd <sup>3</sup>	15.37 m <sup>3</sup>
Capacity Struck - Sideracks	24.7 yd <sup>3</sup>	18.88 m <sup>3</sup>
Max Depth of Cut	7.5 in	190 mm
Ground Clearance @ CE	25.3 in	643 mm
Apron Opening	82 in	2,083 mm

### HYDRAULICS

Bowl Cylinder Bore	8 in	203 mm
Bowl Cylinder Stroke	18 in	457 mm
Apron Cylinder Bore	4.5 in	114 mm
Apron Cylinder Stroke	25.1 in	638 mm
Ejector Cylinder Bore	6 in	152 mm
Ejector Cylinder Stroke	71 in	1803 mm

### BRAKES & TIRES

Brake Type	Dry Disk
Caliper Quantity	4
Tire Quantity	2
Standard Tires	40.5R39

### GROUND PRESSURE\*

Loaded PSI	27.9
Empty PSI	9.7

### WEIGHT DISTRIBUTION

Distribution Empty (Tongue)	28%
Distribution Empty (Axle)	72%
Distribution Loaded (Tongue)	32%
Distribution Loaded (Axle)	68%

### DIMENSIONS

Width (Inside of Bowl)	154 in	3,912 mm
4 Width (Outside Rear Tires)	154 in	3,912 mm
2 Width (Outside Bowl)	166 in	4,216 mm
Height (Floor to top of Ejector)	84 in	2,134 mm
Height (Sidewall)	48 in	1,219 mm
Length (Floor)	70 in	1,778 mm
5 Push Block to Axle	96 in	2,438 mm
6 Axle to Cutting Edge	175 in	4,445 mm
Cutting Edge to Hitch	229 in	5,817 mm
Maximum Load Rating	105,000 lbs	47,600 kg

### SHIPPING MODIFICATIONS

1 Height (Overall Shipping)	140 in	3,556 mm
2 Width (Overall Shipping)	169 in	4,293 mm
3 Length (Overall Shipping)	516 in	13,106 mm
Empty Weight	50,300 lbs	22,800 kg

